



(19)

(11) Publication number:

Generated Document

PATENT ABSTRACTS OF JAPAN

(21) Application number: 10145399

(51) Intl. Cl.: H01B 11/18

(22) Application date: 27.05.98

<p>(30) Priority:</p> <p>(43) Date of application publication: 10.12.99</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: TOTOKU ELECTRIC</p> <p>(72) Inventor: SASAI SHIGEHITO KATAGIRI NAOKI</p> <p>(74) Representative:</p>
--	---

(54) COAXIAL CABLE

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a high frequency use coaxial cable excellent in vibration resistance and shock resistance while having an excellent shielding characteristic over a broad frequency band, is also excellent in durability against bending and has flexibility facilitating termination process.

SOLUTION: In a coaxial cable composed by covering the outside of a central conductor 1 with an insulation 2, two-layer outside conductors 3, 5 and a jacket 6 in that order, this coaxial cable 7 is composed by forming the inner outside conductor 3 by means of spiral lap winding of a rolled metal tape, forming the outer outside conductor 5 of a braided conductor, and interposing a synthetic resin tape wound layer 4 satisfying $0.01 \text{ mm} < t < 0.03 \text{ mm}$ where (t) represents the thickness of the tape wound layer between the inner and outer outside conductors 3, 5.

COPYRIGHT: (C)1999,JPO

